

13. Technical data

Device parameters	Enbio S	Enbio PRO
Power supply	220-240V AC 50/60Hz or 110-120V AC 50/60 Hz	220-240V AC 50 / 60Hz
Installed power	2.25 kW max. or 1.8kW max.	3.25 kW max.
Maximum current consumption	10A or 15A	15 A or 13 A (UK only)
Working pressure	2,1 bar	2,1 bar
Maximum pressure	2,3 bar max	2,3 bar max
Maximum process temperature	137°C	138°C
Process chamber volume	2,7 l	5,3 l
Weight	15 kg	20 kg
Process chamber dimensions (LxWxH)	292 × 192 × 45 mm	300 × 200 × 90 mm
External dimensions of the device (LxWxH)	561 × 252 × 162 mm	561 × 270 × 202 mm
Degree of protection	IP20	IP20
Noise level	38dB(A)	40dB(A)
Archiving process data	Pendrive	Pendrive

Environmental conditions

Working temperature range	from +5°C to +25°C
Relative humidity	0-90%
Storage temperature range	+5°C to + 60°C
Ambient pressure range	900-1100 hPa



Test connector - for use by authorized service only. If found to be used by the user, it will void the warranty.

Rating plate located on the bottom of the device.



Enbio Technology sp. z o.o.
 ul. Działkowców 15
 84-230 Rumia
 Poland